







Bearing type: ⊙=Ball " B" ※=Sleeve " S" ○=1B1S " B(S)" ●=Hypro bearing " X"

| PHOTO | Frame size (mm) | Model No. | Bearing Type | | | | Voltage (v) | Current (A) | Power (W) | Speed (rpm) | Maximum AirFlow | | Maximum Pressure | | Noise (dB/A) | Weight (g) |
|---|-----------------|-------------------|--------------|---|------|---|-------------|-------------|-----------|-------------|-----------------|--------|------------------|--------|--------------|------------|
| | | | B | S | B(S) | X | | | | | (CMM) | (CFM) | (InAq) | (mmAq) | | |
|  | 60X60X25 | AQ0612HB-A70GL(T) | ⊙ | | | | 12 | 0.23 | 2.76 | 4500 | 0.679 | 23.98 | 0.175 | 4.45 | 33.9 | 58 |
| | | AQ0612MB-A70GL(T) | ⊙ | | | | 12 | 0.14 | 1.68 | 3500 | 0.508 | 17.95 | 0.106 | 2.69 | 27.1 | |
| | | AQ0612LB-A70GL(T) | ⊙ | | | | 12 | 0.08 | 0.96 | 2500 | 0.358 | 12.65 | 0.054 | 1.38 | 18.1 | |
|  | 70X70X25 | AQ0712HB-A70GL(T) | ⊙ | | | | 12 | 0.19 | 2.28 | 4200 | 1.016 | 35.86 | 0.220 | 5.60 | 35.5 | 62 |
| | | AQ0712MB-A70GL(T) | ⊙ | | | | 12 | 0.16 | 1.92 | 3800 | 0.915 | 32.33 | 0.180 | 4.40 | 32.0 | |
| | | AQ0712LB-A70GL(T) | ⊙ | | | | 12 | 0.12 | 1.44 | 3300 | 0.803 | 28.37 | 0.140 | 3.45 | 28.0 | |
|  | 80X80X25 | AQ0812HB-A70GL(T) | ⊙ | | | | 12 | 0.25 | 3.00 | 3100 | 1.104 | 39.00 | 0.150 | 3.75 | 34.4 | 82 |
| | | AQ0812MB-A70GL(T) | ⊙ | | | | 12 | 0.15 | 1.80 | 2500 | 0.874 | 30.87 | 0.101 | 2.53 | 28.3 | |
| | | AQ0812LB-A70GL(T) | ⊙ | | | | 12 | 0.12 | 1.44 | 2100 | 0.740 | 26.16 | 0.072 | 1.79 | 22.5 | |
| | | AQ0812DB-A70GL(T) | ⊙ | | | | 12 | 0.09 | 1.08 | 1600 | 0.542 | 19.15 | 0.044 | 1.10 | 15.0 | |
| | | AQ0824MB-A70GL(T) | ⊙ | | | | 24 | 0.10 | 2.40 | 2500 | 0.874 | 30.87 | 0.101 | 2.53 | 28.3 | |
| | | AQ0824LB-A70GL(T) | ⊙ | | | | 24 | 0.09 | 2.16 | 2100 | 0.740 | 26.16 | 0.072 | 1.79 | 22.5 | |
|  | 92X92X25 | AQ0912HB-A70GL(T) | ⊙ | | | | 12 | 0.25 | 3.00 | 2900 | 1.396 | 49.30 | 0.120 | 2.99 | 35.0 | 103 |
| | | AQ0912MB-A70GL(T) | ⊙ | | | | 12 | 0.17 | 2.04 | 2400 | 1.175 | 41.49 | 0.090 | 2.25 | 31.3 | |
| | | AQ0912LB-A70GL(T) | ⊙ | | | | 12 | 0.13 | 1.56 | 2050 | 0.984 | 34.75 | 0.070 | 1.65 | 25.0 | |
|  | 120X120X25 | AQ1212HB-A71GL | ⊙ | | | | 12 | 0.37 | 4.44 | 2200 | 2.51 | 88.71 | 0.136 | 3.45 | 39.1 | 156 |
| | | AQ1212MB-A71GL | ⊙ | | | | 12 | 0.33 | 3.96 | 2050 | 2.36 | 83.21 | 0.119 | 2.98 | 38.0 | |
| | | AQ1212LB-A71GL | ⊙ | | | | 12 | 0.24 | 2.88 | 1800 | 2.28 | 72.00 | 0.095 | 2.37 | 34.4 | |
| | | AQ1224HB-A71GL | ⊙ | | | | 24 | 0.19 | 4.56 | 2200 | 2.51 | 88.71 | 0.136 | 3.45 | 39.1 | |
| | | AQ1224MB-A71GL | ⊙ | | | | 24 | 0.17 | 4.08 | 2050 | 2.36 | 83.21 | 0.119 | 2.98 | 38.0 | |
| | | AQ1224LB-A71GL | ⊙ | | | | 24 | 0.14 | 3.36 | 1800 | 2.28 | 72.00 | 0.095 | 2.37 | 34.4 | |
|  | 120X120X38 | AQ1212DB-F51 | ⊙ | | | | 12 | 0.16 | 1.92 | 1500 | 1.50 | 52.75 | 0.090 | 2.25 | 27.4 | 297 |
| | | AQ1212LB-F51 | ⊙ | | | | 12 | 0.24 | 2.88 | 1950 | 2.07 | 72.66 | 0.127 | 3.17 | 32.9 | |
| | | AQ1212MB-F51 | ⊙ | | | | 12 | 0.35 | 4.20 | 2540 | 2.68 | 94.43 | 0.227 | 5.69 | 41.0 | |
| | | AQ1212HB-F51 | ⊙ | | | | 12 | 0.50 | 6.00 | 2800 | 2.96 | 104.40 | 0.242 | 6.05 | 42.8 | |
| | | AQ1224LB-F51 | ⊙ | | | | 24 | 0.14 | 3.36 | 1950 | 2.07 | 72.66 | 0.127 | 3.17 | 32.9 | |
| | | AQ1224MB-F51 | ⊙ | | | | 24 | 0.23 | 5.52 | 2540 | 2.68 | 94.43 | 0.227 | 5.69 | 41.0 | |
| | | AQ1224HB-F51 | ⊙ | | | | 24 | 0.32 | 7.68 | 2800 | 2.96 | 104.40 | 0.242 | 6.05 | 42.8 | |
| | | AQ1248DB-F51 | ⊙ | | | | 48 | 0.08 | 3.84 | 1500 | 1.50 | 52.75 | 0.090 | 2.25 | 27.4 | |
| | | AQ1248LB-F51 | ⊙ | | | | 48 | 0.10 | 4.80 | 1950 | 2.07 | 72.66 | 0.127 | 3.17 | 32.9 | |
| | | AQ1248MB-F51 | ⊙ | | | | 48 | 0.14 | 6.72 | 2540 | 2.68 | 94.43 | 0.227 | 5.69 | 41.0 | |
| | | AQ1248HB-F51 | ⊙ | | | | 48 | 0.20 | 9.60 | 2800 | 2.96 | 104.40 | 0.242 | 6.05 | 42.8 | |

Specifications subject to change without notice.